

Specifications

Specification/Model	ECO-BR20CC-8-27K	ECO-BR30CC-9-27K	ECO-BR30CC-14-27K	ECO-BR40CC-15-27K	ECO-BR40CC-17-27K				
Input Power	8W	9W	14W	15W	17W				
Lumens output	550lm	680lm	1070lm	1070lm	1300lm				
Efficacy	69 lm/W	76 lm/W	82 lm/W	71 lm/W	76 lm/W				
CRI	82								
Color Temperature	2700K								
Input Voltage	120VAC	120VAC	120VAC	120VAC	120VAC				
Beam angle	120°	120°	120°	120°	120°				
Energy Efficiency	50W	65W	85W	75W	120W				
Finish Color	White								
Dimmable	100% to 10%								
Suitable for Enclosed/ Recessed Fixture	Suitable for recessed fixture								



Ordering Guide

EXAMPLE: <u>ECO-BR20CC-8-27K</u>

Lamp Type	Power Consumption	Lamp Base	сст	Series	Finish	CRI				
BR20	8 8Watts	E26 E26 base	27K 2700K	CC	W White	CRI80				
BR30	9 9Watts		30K 3000K							
BR40	14 14Watts		40K 4000K							
	15 15Watts		50K 5000K							
	17 17Watts		60K 6000K							

Features

· UL listing

UL listed for damp locations

• Energy Star

Energy Star qualified at 2700K, 3000K and 4000K

• LEDS

LM-80 certified high performance and reliable Lumileds LEDS

Drivers

Compatible with most dimmers, no flickering

Housing and Finish

Die-cast aluminum housing with white coat finish

· Ambient Temperature

Suitable for use in -25 °C to 30 °C

Warranty

5 year limited warranty

Applications

Residential, retail, restaurants, hotels, jewelry stores, shopping malls, museums, etc....

Dimensions

umit. mm















