

Eco-Story LED MR Series



Ordering Guide

EXAMPLE: ECO-MR16CC-7-27K-40D

Lamp Type	Power Consumption	CCT	Beam angle	Series	Finish	CRI
MR16 GU10 MR16 PAR16	7 7Watts	27K 2700K 30K 3000K 40K 4000K 50K 5000K	25D 25° 40D 40°	MR16CC MR16GUCC PAR16CC	W White	CRI80 CRI90

Specification

Specification/Model	ECO-MR16CC-7-27K-40D	ECO-MR16CC-GU-7-27K-40D	ECO-PAR16CC-7-27K-40D
Input Power	7W	7W	7W
Lumens output	450lm	500lm	500lm
Efficacy	64 lm/W	71 lm/W	71 lm/W
CRI	90	90	90
Color Temperature	2700K		
Input Voltage	AC/DC 12V	120VAC	120VAC
Beam angle	40°	40°	40°
CBCP	1300 cd		
Equivalent	50W Halogen		
Finish Color	White		
Dimmable	100% to 10%		

Features

- UL listing**
 UL listed for damp location and suitable for Enclosed Fixture
- Energy Star**
 Energy Star qualified at 2700K, 3000K, 4000K
- LEDS**
 LM-80 certified high performance and reliable LEDES
- Drivers**
 Compatible with most dimmers, no flickering
- Housing and Finish**
 Die-cast aluminum housing with white coat finish
- Optical Lens**
 Full face optics with high transmittance
- Ambient Temperature**
 Suitable for use in -25°C to 30°C
- Warranty**
 5 year limited warranty

Applications

Residential, retail, restaurants, hotels, jewelry stores, shopping malls, museums, etc...

Dimensions

unit: mm

MR16

GU10

PAR16

