

Eco-Story LED Architecture Troffer

Features

- Available in 2'x2' 35W and 2'x4' 42W for recessed installation
- Lumen output from 2000-4000lm with efficacy of 100lm/W.
- White powder coated steel housing improves the efficacy of the fixtures.
- Built-in earthquake clips for safety.
- 1-10V Dimmable.
- UL and DLC Listed.



Applications

- Offices, schools, hospitals and all other commercial applications.



Specification

Specification/Model	ECOTF22D35W50	ECOTF24D42W50K
Input Power	35W	42W
Lumens output	3150lm	4200lm
Efficacy	90 lm/W	100 lm/W
CRI	80	
Color Temperature	5000K	
Input Voltage	120-277VAC	120-277VAC
Finish Color	White	
Mounting	Recessed	
Equivalent	2 x 32W U-Bend	2 x 32W T8

Ordering Guide

EXAMPLE : ECO TF 22D 35W 50K _____

Lamp Type	Style	Arcuate Number	Size	Power Consumption	Input Voltage	CCT	CRI
TF Troffer	AR Arcuate	S Single	22D 2x2 foot	35W 35Watts	27V 120-277V	35K 3500K	H 80CRI
		D Double	24D 2x4 foot	42W 42Watts		40K 4000K	
						50K 5000K	

Dimensions

unit: mm



