

Eco-Story LED Vapor Tight Fixtures



Features

- Suitable for WET locations
- High efficiency 123lm+/W
- Stainless Steel clip for easy cable or chain attachment
- Ceiling or Wall mounted
- True UL 94 Flame Rating - 5VA rating on housing
- Backup Battery and Motion Sensor options available
- UL/cUL listed and DLC qualified



Applications

- Parking garages, food processing, corrosive and/or wet locations



Specification

Specification/ Model	ECOV ^T 30W2D50K	ECOV ^T 40W4D50K	ECOV ^T 55W4D40K	ECOV ^T 80W8D50K	ECOV ^T 110W8D50K
Input Power	30	40	55	80	110
Lumens output	4000	5150	6750	10300	13500
Efficacy	133	129	123	129	105
CRI	82				
Color Temperature	5000				
Input Voltage	120-277	120-277	120-277	120-277	120-277
Finish Color	White				
Lens	Polycarbonate (UL Recognized) (f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion				
Mounting	Wall or Chain Mounted				
Motion Sensor (optional)	120-277V				
Backup Battery (optional)	90min				

Ordering Guide

EXAMPLE : ECO VT 30W 2D 40K M B _

Luminaire Type	Power Consumption		Voltage		Dimension		CCT		Accessory (Option)	Accessory (Option)
VT Vapor Tight Light	30W	30 Watts	27V	120-277V	2D	2 Foot	40K	4000K	(Blank) Without Motion Sensor M Motion Sensor	B Backup Battery Blank Without Backup Battery
	40W	40Watts			4D	4 Foot	50K	5000K		
	55W	55Watts			8D	8 Foot				
	80W	80Watts								
	110W	110Watts								

Dimension

unit: mm/inch

